



## MATERIAL SAFETY DATA SHEET

### TEXTURE COAT

#### 1. Identification

**GHS product identifier:**

TEXTURE COAT

**Other means of identification:**

A coarse, textured weather resistant paint.

**Relevant identified uses of the substance or mixture and uses advised against**

Identified uses:

Weatherproofing and decorating exterior wall surfaces. Also used to disguise minor surface irregularities in the substrate. For application to well cleaned, prepared and primed concrete, cement plaster and other masonry surfaces.

**Supplier's details:**

Pro-Paint Manufacturing (PTY) LTD  
4 Industrial Crescent  
Bronkhorstspuit  
1020

**Emergency phone:**

013 932 0020 (within hours of operation)

#### 2. Hazards identification

**Classification of the substance or mixture**

Not classified as hazardous.

**Label elements according to:**

SANS 10234: 2008

Hazard pictograms: None required

Signal word: Warning

Hazard statements: H303- May be harmful if swallowed.

H313- May be harmful in contact with skin.

H333- May be harmful if inhaled.

H413- May cause long-lasting harmful effects to aquatic life.

#### Precautionary statements

General :

P101- If medical advice is needed, have product container or label at hand.

P102- Keep out of reach of children.

P103- Read label before use.

Prevention :

P202- Do not handle until all safety precautions have been read and understood



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure.  
April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.



Response:

- P501: Dispose of contents/containers in accordance with local regulation.
- P233- Keep container tightly closed.
- P261- Avoid breathing vapours/spray.
- P262- Do not get in eyes, on skin, or on clothing.
- P270- Do not eat, drink or smoke when using this product.
- P271- Use only outdoors or in a well-ventilated area.
- P273- Avoid release to the environment.
- P280- Wear protective gloves/protective clothing/eye protection/face protection
- P285- In case of inadequate ventilation wear respiratory protection.
- P235+410- Keep cool. Protect from sunlight.
- P314- Get medical advice/attention if you feel unwell.
- P391- Collect spillage.
- P301+330+331- IF SWALLOWED- Rinse mouth. Do NOT induce vomiting.
- P303+361+353- IF ON SKIN (or hair)- Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P304+340: IF INHALED- Remove person to fresh air and keep comfortable for breathing.
- P305+351+338- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
- P333+313- If skin irritation or a rash occurs: Get medical advice/attention.
- P337+313- If eye irritation persists get medical advice/attention.
- P362+364- Take off contaminated clothing and wash it before reuse.
- P410- Protect from sunlight.
- P402+404- Store in a dry place. Store in a closed container.
- P403+235- Store in a well ventilated place. Keep cool.

Storage:

**Other hazards which do not result in classification:**

None identified



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure.  
April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.



### **3. Composition/information on ingredients**

**Substance/mixture:** Mixture  
**Other means of identification:** Emulsion based paint  
**CAS number/other identifiers**  
CAS number: Not applicable

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.**

### **4. First aid measures**

Description of necessary first aid measures

**Eye contact:** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.

**Inhalation:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.

**Skin contact:** Wash contaminated skin with soap or a recognised skin cleaner and plenty of water. Avoid the use of solvents. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

**Ingestion:** Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

### **Most important symptoms/ effects, acute and delayed**

Potential acute health effects

**Eye contact:** May cause eye irritation.  
**Inhalation:** May be harmful if inhaled.  
**Skin contact:** May cause skin irritation.  
**Ingestion:** May be harmful if swallowed.

Over-exposure signs/symptoms



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure.  
April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.



Eye contact: Adverse symptoms may include pain or irritation, watering or redness.

Inhalation: Adverse symptoms may include nausea or vomiting, headache, drowsiness /fatigue or dizziness/vertigo.

Skin contact: Adverse symptoms may include irritation or redness.

Ingestion: No data available.

**Indication of immediate medical attention and special treatment needed, if necessary**

Notes to physician: Treat symptomatically. Contact poison treatment specialist immediately If large quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training.

**See toxicological information (Section 11)**

## **5. Fire-fighting measures**

### **Extinguishing media**

Suitable extinguishing media:

Use an extinguishing agent suitable for the surrounding fire such as foam, CO2 or dry powder.

Unsuitable extinguishing media:

None known.

### **Specific hazards arising from from the chemical:**

In a fire or if heated, a pressure increase will occur and the container may burst. Dried residues may be combustible.

### **Hazardous thermal decomposition products:**

Decomposition products may include the following materials:

carbon dioxide  
carbon monoxide  
metal oxide/oxides

### **Special protective actions For fire-fighters:**

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure.  
April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.



## Special protective

### equipment for fire-fighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel:

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions:

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

Small spill:

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill:

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure.  
April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.



spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.

## **7. Handling and storage**

### **Precautions for safe handling:**

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist.

### **Conditions for safe storage, including any incompatibilities:**

**Store** in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Do not reuse container.

## **Section 8. Exposure controls/personal protection**

### **Occupational exposure limits:**

None.

### **Recommended monitoring**

### **Procedures:**

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure.  
April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.



**Appropriate engineering controls:**

determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

**Environmental exposure controls:**

Emissions from ventilation or work process equipment Should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**Individual protection measures**  
Hygiene measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection:

Avoid direct contact. Never touch eyes with dirty hands or gloves. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Hand protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure.  
April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.



Body protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection:

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary e.g. in case of insufficient ventilation. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## **9. Physical and chemical properties**

Physical state:

Viscous Liquid

Colour:

White (UTX 1); Cream (UTX 2); Beige (UTX 3); Peach (UTX 4); Tan (UTX 5); Sand (UTX 6); Fern (UTX 7); Grey (UTX 8).

Odour:

No data available.

Odour threshold:

No data available.

pH:

8.5 – 9.0

Melting point:

No data available.

Boiling point:

No data available.

Flash point:

Product does not sustain combustion.

Evaporation rate:

No data available.

Flammability (solid, gas):

Not applicable.

Lower and upper explosive (flammable) limits:

Not applicable.

Vapor pressure:

No data available.

Vapor density:

No data available.

Relative density:

1.3 (typical)

Solubility:

Water miscible

Partition coefficient, n-octanol/water:

No data available.



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure.  
April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.





Auto-ignition temperature:  
Decomposition temperature:  
Viscosity:

No data available.  
No data available.  
105-118 KU

## **10. Stability and reactivity**

**Reactivity:**

Inert - no reaction with fire-fighting water.  
Stable under normal conditions.

**Chemical stability:**

**Possibility of hazardous reactions:**

Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid:**

Avoid contact with acids, alkalis and hydrocarbon solvents.

**Incompatible materials:**

No data available.

**Hazardous decomposition products:**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **Section 11. Toxicological information**

Information on the likely routes of exposure:

Inhalation, skin contact

Potential acute health effects

Eye contact:

May cause eye irritation.

Inhalation:

May be harmful if inhaled.

Skin contact:

May cause skin irritation.

Ingestion:

May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact:

Adverse symptoms may include pain, irritation, watering or redness.

Inhalation:

Adverse symptoms may include nausea or vomiting, headaches, drowsiness/fatigue or dizziness/vertigo.

Skin contact:

Adverse symptoms may include irritation or redness.

Ingestion:

No data available.



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure.  
April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.



General:

Potential Chronic health effects

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity:

No known significant effects or critical hazards.

Mutagenicity:

No known significant effects or critical hazards.

Teratogenicity:

No known significant effects or critical hazards.

Developmental effects:

No known significant effects or critical hazards.

Fertility effects:

No known significant effects or critical hazards.

Acute toxicity estimates

No data available.

## **12. Ecological information**

### **Toxicity**

No data available.

### **Persistence and degradability**

No data available.

### **Bioaccumulate potential**

No data available.

### **Mobility in soil**

Soil/ water partition coefficient (KOC):

No data available.

Mobility: No data available.

### **PBT/pub data:**

P: No data available. B: No data available. T: No Data available.

### **Other adverse effects:**

No known significant effects or critical hazards.

## **13. Disposal considerations**

### **Disposal methods:**

This material and its container must be disposed of in a safe way. The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure.  
April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.



should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**14. Transport information**

	<b>Transportation - road - SANS 10228:2012</b>	<b>Transportation- Maritime - IMO/ IMDG</b>	<b>Transportation- Air - IATA</b>
<b>UN number</b>	Not regulated	Not regulated	Not regulated
<b>UN proper shipping name</b>	No data available	No data available	No data available
<b>Transport hazard class(es)</b>	No data available	No data available	No data available
<b>Packing group</b>	No data available	No data available	No data available
<b>Marine pollutant</b>	No	No	No
<b>Additional information</b>	No data available	No data available	No data available
<b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code</b>	No data available	No data available	No data available

**Section 15. Regulatory information**

**Safety, health and environmental regulations**

**specific for the product: Relevant information regarding authorization:**

Occupational Health and Safety Act 1993 Regulation for Hazardous Chemical Substances.

**Relevant information regarding restrictions:**

None known.

**EU regulations:**

Regulation EC 1272/2008 [EU-GHS/CLP] and EU



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure. April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.



#### Other National regulations:

directives 67/548/EEC or EC 1999/45/EC  
None. Standards used for PPE  
recommendations in Section 8: NIOSH-National Institute for Occupational Health and Safety (USA) EN 166- European standard which concerns the area of eye protection. EN 374-3 European standards for permeation and penetration. EN 141/EN 143 European standards for gas mixtures to remove specified gases and vapours or combined filters for removing solids, and/or liquid particles and specified gases and vapours.

#### 16. Other information

##### Key to abbreviations:

ATE = Acute Toxicity Estimate  
BCP Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
Log Pow = logarithm of the octanol/water partition coefficient  
MARPOL 73/78 = International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978. ("Marplot" = marine pollution)  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
UN = United Nations  
Supplier safety data sheets

##### References :

##### Further information:

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

##### Notice to readers:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure.  
April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.



the health and safety of employees.

This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

**Legal disclaimer:**

The above information is believed to be correct but does not purport to be all inclusive and shall be only used as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure.  
April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.