



# MATERIAL SAFETY DATA SHEET

## INDUSTRIAL QUICK DRY PRIMER ETCH COAT

### 1. COMPANY IDENTIFICATION

NAME: Pro-Paint Manufacturing (PTY) LTD  
ADDRESSES: 4 Industrial Crescent                      4 Kort Street  
Bronkhorstspuit                                      Louis Trichardt  
1020    0920  
Gauteng    Limpopo  
South Africa    South Africa  
TEL: 013 932 0020    015 518 4053

### 2. PRODUCT DETAILS

TRADE NAME: Etch Coat  
MAIN USE: See Technical Data Sheets.  
CHEMICAL FAMILY: PVB and modified alkyd resin.  
CHEMICAL NAME: Short oil air drying alkyd resin.

### 3. HAZARDS IDENTIFICATION

HUMAN HEALTH HAZARDS: Not classified as dangerous under EC criteria.  
SAFETY HAZARDS: Flammable, vapours may cause drowsiness and dizziness.  
ENVIRONMENTAL HAZARDS: No specific hazard.  
HAZARDOUS COMPONENT: Aromatic Solvent Blend: Chemical Name - Solumix.

### 4. FIRST AID MEASURES

INHALATION: Remove to ventilated area, in severe case call Physician.  
INGESTION: Do not induce vomiting, drink water and seek medical attention.  
EYE: Treat same as for solvent in eyes, flush thoroughly with water.  
SKIN: Wash with soap and water. Remove contaminated clothing.  
SYMPTOMS AND EFFECTS: Not expected to give rise to an acute hazard under normal condition of use.



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure.  
April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.



## 5. FIRE FIGHTING MEASURES

SPECIFIC HAZARD:	Flammable, flash point 18°C - 28°C.
EXTINGUISHING MEDIA:	Carbon Dioxide, Foam, Dry Chem.
SPECIAL FIRE FIGHTING:	Use foam to contain.
PROTECTIVE EQUIPMENT:	Basic protective clothing and respirator mask.

## 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:	Excluding sources of ignition and ventilate the area. Avoid breathing vapour or mist.
PERSONAL PROTECTION:	Wear protective gloves, overalls, footwear and respiratory equipment.
ENVIRONMENTAL AREA:	Do not wash into drains or watercourses.
SPILLS:	Contain and collect spillage with non-combustible absorbent material, e.g. sand, earth and place in container for safe disposal.

## 7. HANDLING AND STORAGE

HANDLING:	Keep container tightly closed. Keep away from all ignition sources. Comply with health and safety regulations when applying this product. Use in well ventilated areas.
STORAGE:	Store in a cool well-ventilated area away from incompatible material and ignition sources.

## 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE:	None established.
ENGINEERING CONTROL MEASURES:	Provide adequate ventilation.
PERSONAL PROTECTION	Breathing apparatus if ventilation not adequate.
-RESPIRATORY:	Face shield or safety goggles recommended.
-EYE:	Overalls to protect against splashes.
-SKIN:	Do not eat drink and smoke when handling.
-OTHER:	

## 9. PHYSICAL & CHEMICAL PROPERTIES

PHYSICAL STATE:	Dispersed pigment in relevant resin mixture.
ODOUR:	Characteristic.
COLOUR:	As supplied.
PH:	6-8
DENSITY:	0,9 – 1,1
TYPICAL PROPERTIES:	Refer to Technical Data Sheet.



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure.  
April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.



SOLUBILITY:

Soluble in alcohols and various aromatic solvents. Not soluble in water

## 10. STABILITY & REACTIVITY

STABILITY:

Stable under recommended conditions of storage.

CONDITIONS TO AVOID:

Extreme heat and cold.

INCOMPATIBILITY:

Strong Oxidisers.

HAZARDOUS DECOMPOSITION:

Carbon Monoxide.

## 11. TOXOLOGICAL INFORMATION

BASIS FOR ASSESSMENT:

Information given is based on knowledge of the constituents and the toxicology of similar substances.

ACUTE TOXICITY-ORAL:

LD 50>2000mg/kg.

ACUTE TOXICITY-DERMAL:

LD 50>2000mg/kg.

IRRITATION:

-RESPIRATORY:

Irritant.

-EYE:

Irritant

-SKIN:

Irritant and could cause Dermatitis.

## 12. ECOLOGICAL INFORMATION

BASIS OF ASSESSMENT:

Incomplete eco-toxicological data are available for this substance.

MOBILITY:

Sinks in water.

PERSISTENCE/DEGRADABILITY:

Not biodegradable.

ECO-TOXICITY:

Moderate to High Toxicity to aquatic organisms. No lead or arsenic compounds.

## 13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS:

Waste or spillage should not be discharged into drains.

DISPOSAL OF CONTAINERS:

Puncture to prevent reuse. Remove all packaging for recovery or waste disposal.

LOCAL LEGISLATION:

Occupational Health & Safety Act  
Hazardous Chemical Substances Regulation Section 15

## 14. TRANSPORT INFORMATION

Not dangerous for conveyance under UN, IMO, ADR/RID & IATA/CAO Codes.

LOCAL REGULATIONS:

SABS 0228-1995 & SABS 0229-1990, Packaging of Dangerous goods for road & Rail Transportation in South Africa.  
SABS 0232-1995. Transportation of Dangerous Goods.



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure.  
April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.



Emergency information systems part 1, Emergency information Systems for road transportation.

## 15. REGULATORY INFORMATION

EC CLASSIFICATION:

Flammable, Dangerous for the Environment.

EC RISK PHRASES:

R10 – Flammable.

R67 – Vapours may cause drowsiness and dizziness.

R51/53 – Toxic to aquatic organisms, may have long term adverse effects on aquatic organisms.

EC SAFETY PHRASES:

S16 – Keep away from source of ignition-no smoking.

S23 – Do not breathe vapour / spray.

S51 – Use in well ventilated areas.

S57 – Use appropriate containment to avoid environmental contamination.

S61 – Avoid Release to the environment. Refer to data sheet.

## 16. OTHER INFORMATION

The information is based on our current knowledge and is intended to describe the product. This information is for the purpose of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.



**PROTECTION WHERE YOU NEED IT!**

Limitation of liability applies. Refer to annexure for full disclosure.  
April 2009 - INDUSTRIAL RANGE - HB EPOXY PIPE COAT - revision 1 of 2009.